

DECLARATION OF PERFORMANCE: N° BP033000-01GB

1. Unique identification code of the product-type: **NOVA_ISOROOF_PLUS_MINERAL**

2. Intended use or uses of the constructoin product:

European Standard UNI EN	Intended use
EN13707:2004 +A2:2009	Flexible sheets for waterproofing. Reinforced bitumen sheets for roof waterproofing
EN13969:2004 /A1:2006	Flexible sheets for waterproofing. Bitumen damp proof sheets including bitumen basement tanking sheets

3. Manufacturer name, registered trade name:

NOVAGLASS Spa via Gattolè, 1 Salgareda (TV) tel: +39 04228084 fax +39 0422807882 email info@novaglass.com

4. Authorised representative:

not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product:

European Standard UNI EN	Systems of assessment and verification of constancy of performance of the construction product (AVCP)
EN13707:2004 +A2:2009	2+
EN13969:2004 /A1:2006	2+

6. In accordance with AVCP the above-mentioned systems, institutes/laboratories reported have performed the initial inspection, verification of system control, monitoring and evaluation, verification of control of production, the initial type testing provided the end of the visit they released certificate of conformity of the control system factory:

European Standard UNI EN	Notify Body / Institute	Accreditation number	Certificate / Report
EN13707:2004 +A2:2009; EN13969:2004 /A1:2006	SGS	0120	GB 06/69407 26/07/2006

6b. European technical assessment: not applicable

7. Declared performance:

Essential characteristic	EN Norm	Unit	Tolerance	Performance	European Standard UNI EN
Flexibility at low temperature (pliability)	EN1109	°C	<=	-15	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
Heat flow resistance	EN1110	°C	>=	90	EN13707:2004 +A2:2009
Watertightness	EN1928-B	kPa	>=	100	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
Tensile properties: maximum tensile strength	EN12311-1	N/50 mm	-20%	550 350	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
Tensile properties: elongation at break	EN12311-1	%	-15	35 35	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
Resistance to tearing (nail shank)	EN12310-1	N	-30%	100 100	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
Dimensional stability	EN1107-1	%	<=	±0,3 ±0,3	EN13707:2004 +A2:2009
Shear resistance of joints	EN12317-1	N/50 mm	-20%	550 350	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
Resistance to static puncture	EN12730-A	kg	>=	NPD	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
Resistance to impact	EN12691-A	mm	>=	NPD	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
External fire performance	EN1187/EN13501-5+A1	Class	-	Roof	EN13707:2004 +A2:2009
Reaction to fire	EN11925-2/EN13501-1+A1	Class	-	F	EN13707:2004 +A2:2009; EN13969:2004 /A1:2006
Determination of adhesion of granules (Loss)	EN12039	%	<30	PASSED	EN13707:2004 +A2:2009
Visible defects	EN1850-1	-	-	PASSED	EN13707:2004 +A2:2009
Durability: Flexibility at low temperature after artificial ageing	EN1296/EN1109	°C	+15	-5	EN13707:2004 +A2:2009
Durability: Flow resistance at elevated temperature after artificial ageing	EN1296/EN1110	°C	-10	NPD	EN13707:2004 +A2:2009
Durability: Watertightness after artificial ageing	EN1296/EN1928-B	kPa	>= 60	PASSED	EN13969:2004 /A1:2006
Durability: Watertightness against chemicals	EN1296/EN1847	-	PASSED	NPD	EN13969:2004 /A1:2006
Dangerous substances free (1)	It does not contain asbestos or tar				

Note (1): In the absence of European harmonized test methods, verification and declaration on release/content will be made taking into account national provisions

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Salgareda, 01/07/2013

Chairman and Legal Representative of:

Luca De Leo



Rev. 1 del 01/10/2015